

# (H)05VV5-F ((N)YSLYÖ-JZ) flexible, number coded, oil resistant, meter marking



## Technical data

- Control cable, special PVC with oil resistant outer jacket adapted to VDE 0281 part 13, HD 21.13S1 and IEC 60227/75 deviation of conductor cross sections.
- Temperature range**  
flexing -5 °C to +70 °C  
fixed installation -40 °C to +70 °C
- Nominal voltage** U<sub>0</sub>/U 300/500 V
- Test voltage** 2000 V, 5 min
- Breakdown voltage** min. 4000 V
- Insulation resistance**  
min. 20 MOhm x km
- Minimum bending radius**  
flexing 7,5x cable Ø  
fixed installation 4x cable Ø
- Radiation resistance**  
up to 80x10<sup>6</sup> cJ/kg (up to 80 Mrad)

## Cable structure

- Bare copper, fine wire stranded conductor to DIN VDE 0295 cl. 5, BS 6360 cl. 5, IEC 60228 cl. 5 and HD 383
- Special PVC core insulation TI2 to DIN VDE 0281 part 1
- Black cores with white figure imprint to DIN VDE 0293
- Green-yellow earth core in the outer layer (3 cores and above)
- Cores stranded in layers with optimal lay-length
- Special PVC outer jacket, TM5 to DIN VDE 0281 part 1, HD 21.1.S4/A16
- Colour grey (RAL 7001)
- with meter marking, change-over in 2011

## Properties

- PVC self-extinguishing and flame retardant according to DIN VDE 0482 part 265-2-1/ EN 50265-2-1/ IEC 60332-1 (equivalent DIN VDE 0472 part 804 test method B)
- Oil resistant to DIN EN 60811-2-1
- The materials used in manufacture are cadmium-free and contain no silicone and free from substances harmful to the wetting properties of lacquers

## Note

- G = with green-yellow earth core;  
x = without green-yellow earth core (OZ).
- AWG sizes are approximate equivalent values. The actual cross-section is in mm<sup>2</sup>.
- screened analogue type:**  
**(H)05VVC4V5-K**, see page A 31

## Application

These cables are used for flexible use for medium mechanical stresses with free movement without tensile stress or forced movements in dry, moist and wet rooms but not suitable for open air. These are designed as control and connecting cables to machines, tool machineries, conveyor belts and production lines.

These cables are not effected to the chemical influences. Cables for moist and wet rooms, specially used for machines in breweries, bottling plants and car washing stations.

CE The product is conformed with the EC Low-Voltage Directive 2006/95/EG.

Part no.	No. cores x cross-sec. mm <sup>2</sup>	Outer Ø approx. mm	Cop. weight kg / km	Weight approx. kg / km	AWG-No.
13133	2 x 4	10,7	77,0	195,0	12
13134	3 G 4	11,3	115,0	230,0	12
13135	4 G 4	12,4	154,0	295,0	12
13136	5 G 4	13,9	192,0	361,0	12
13138	7 G 4	16,6	269,0	466,0	12
13141	12 G 4	20,8	461,0	810,0	12
13142	2 x 6	12,0	116,0	280,0	10
13143	3 G 6	12,9	173,0	358,0	10
13144	4 G 6	14,2	230,0	424,0	10
13145	5 G 6	15,9	288,0	525,0	10
13146	7 G 6	18,9	403,0	625,0	10
13148	3 G 10	16,3	288,0	540,0	8
13149	4 G 10	18,1	384,0	701,0	8
13150	5 G 10	20,3	480,0	858,0	8
13151	7 G 10	24,3	672,0	1106,0	8

Part no.	No. cores x cross-sec. mm <sup>2</sup>	Outer Ø approx. mm	Cop. weight kg / km	Weight approx. kg / km	AWG-No.
13153	3 G 16	18,8	461,0	827,0	6
13154	4 G 16	20,9	614,0	1035,0	6
13155	5 G 16	23,4	768,0	1259,0	6
13156	7 G 16	28,5	1075,0	1780,0	6
13159	4 G 25	26,3	960,0	1582,0	4
13160	5 G 25	29,5	1200,0	1852,0	4
13161	3 G 35	26,5	1008,0	1614,0	2
13162	4 G 35	29,5	1344,0	2110,0	2
13163	5 G 35	32,8	1680,0	2652,0	2
13164	3 G 50	32,2	1440,0	2560,0	1
13165	4 G 50	36,1	1920,0	2972,0	1
13166	5 G 50	40,3	2400,0	3948,0	1

Dimensions and specifications may be changed without prior notice. (RA01)